Author Manuscript

- **Title:** Tunable Syngas Production from CO2 and H2O in an Aqueous Photoelectrochemical Cell
- Authors: Sheng Chu; Shizhao Fan; Yongjie Wang; David Rossouw; Yichen Wang; Gianluigi A. Botton; Zetian Mi

This is the author manuscript accepted for publication and has undergone full peer review but has not been through the copyediting, typesetting, pagination and proofreading process, which may lead to differences between this version and the Version of Record.

To be cited as: 10.1002/anie.201606424

Link to VoR: http://dx.doi.org/10.1002/anie.201606424

Tunable Syngas Production from CO₂ and H₂O in an Aqueous Photoelectrochemical Cell

Sheng Chu, Shizhao Fan, Yongjie Wang, David Rossouw, Yichen Wang, Gianluigi A. Botton and Zetian Mi*

Abstract: Syngas, the mixture of CO and H₂, is a key feedstock to produce methanol and liquid fuels in industry, yet limited success has been made to develop clean syngas production using renewable solar energy. We demonstrated that syngas with a benchmark turnover number of 1330 and a desirable CO/H₂ ratio of 1 : 2 could be attained from photoelectrochemical CO₂ and H₂O reduction in an aqueous medium by exploiting the synergistic co-catalytic effect between Cu and ZnO. The CO/H₂ ratio in the syngas products was tuned in a large range between 2 : 1 and 1 : 4 with a total unity Faradaic efficiency. Moreover, a high Faradaic efficiency of 70% for CO was acheived at underpotential of 180 mV, which is the lowest potential ever reported in an aqueous photoelectrochemical cell. It was found that the combination of Cu and ZnO offered complementary chemical properties that lead to special reaction channels not seen in Cu, or ZnO alone.

Syngas (synthesis gas, CO+H₂ mixtures) is a critical C1 feedstock to produce methanol and synthetic liquid fuels via established industrial process.^[1] For practical applications, the CO/H₂ ratio in syngas mixtures is important to meet the requirements for different downstream products (1:2 and 1:1 for methanol and dimethyl ether, respectively). To date, syngas is predominantly derived from non-renewable fossil sources such as natural gas and coal. CO₂ is a useful carbon source for fuel or chemical synthesis due to its abundance, availability, nontoxicity and recyclability.^[2] Using energy from a renewable source (e.g. solar energy) to reduce CO₂ and H₂O offers an alternate, sustainable and carbon-neutral approach for obtaining syngas mixtures.^[3] Recently, the photoelectrochemical (PEC) route, which mimic natural photosynthsis to directly convert light energy into storable chemical energy at ambient conditions, has attracted substantial interests for application in CO2 reduction.^[4] To date, a range of semiconductors, including p-Si,^[5] p-CdTe,^[6] p-InP ^[6] and ZnTe ^[7], usually in combination with an effective metal co-catalyst (e.g. Au, Ag and Cu), have been investigated for selective CO formation from CO2 reduction in an aqueous PEC cell. The device performance, however, often suffers from the following

 [a] Dr. S. Chu, Dr. S. Fan, Dr. Y. Wang, Prof. Z. Mi Department of Electrical and Computer Engineering McGill University
 3480 University Street, Montreal, QC H3A 0E9, Canada

- [b] Y. Wang, Prof. Z. Mi Department of Electrical and Computer Science Center for Photonics and Multiscale Nanomaterials University of Michigan, Ann Arbor 1301 Beal Avenue, Ann Arbor, MI 48105, USA E-mail: <u>ztmi@umich.edu</u>
- [c] Dr. D. Rossouw, Prof. G. A. Botton
 Department of Materials Science and Engineering
 McMaster University
 1280 Main Street West, Hamilton, Ontario L8S 4L7, Canada

fundamental limitations, including impractically high overpotential (typically > 0.5 V) to activate the inert and very stable CO₂ molecule, and low selectivity towards CO due to the similarity in reduction potentials of competitive H₂ evolution reaction and the formation of other CO₂ reduction products (e.g. HCOOH, CH₄). Thus, it is highly desirable to develop high-efficiency materials system with controlled selectivity for CO₂ reduction towards CO at low overpotential or even underpotential without any external electrical bias.

In this work, we demonstrate that a monolithically integrated photocathode, by coupling Cu and ZnO as dual co-catalysts with the strong light harvesting of p-n junction Si and efficient electron extraction effect of GaN nanowire arrays (Cu-ZnO/GaN/n⁺-p Si), can efficiently produce syngas from CO₂ and H₂O reduction in an aqueous PEC cell. The CO/H₂ ratio in the syngas product could be adjusted in a large range between 2 : 1 and 1 : 4 with a total unity Faradaic efficiency (FE). Moreover, a benchmark turnover number of 1330 and a high FE of 70% for CO at underpotential of 180 mV were achieved. Additionally, the photocathode exhibited superior stability for syngas production under constant illumination for 10 h. Interestingly, it was found that the combination of Cu and ZnO offered synergetic effects that lead to special reaction pathways not seen in Cu or ZnO alone.

The design of Cu-ZnO/GaN/n⁺-p Si photocathode is schematically illustrated in Figure 1a. The sample was synthesized in two steps. First, one-dimensional (1D) GaN nanowire arrays were grown on p-n junction Si wafer by plasmaassisted molecular beam epitaxy. Such a structure takes advantage of the strong light absorption capability of p-n junction Si and efficient electron extraction effect provided by GaN nanowires.^[8] In addition, GaN exhibits a high level of photostability in aqueous solution.^[9] and the nanowire arrays can enhance the light absorption due to the anti-reflection effect.^[10] Second, two-dimensional (2D) ZnO nanosheets and zerodimensional (0D) Cu nanoparticles were photodeposited on the upper parts of GaN nanowires via a simple wet chemical process (see Supporting Information for experimental details). The energy band diagram of the composites under illumination is depicted in Figure S1. In this multi-dimensional heterostructure, the p-n junction Si can absorb a large number of photons up to wavelengths of 1100 nm due to its narrow band gap ($E_{q} \sim 1.1 \text{ eV}$), while the photogenerated electrons in the Si can be readily injected and transport via the 1D GaN nanowires to 2D ZnO nanosheets due to the small conduction band offsets between them. ZnO could perfectly align with GaN due to their similar crystal structure and very close lattice match.[11] Therefore, ZnO may form promising junction with GaN to facilitate the transport of photogenerated electrons.^[12] Moreover, ZnO has excellent properties to adsorb and activate inert CO2 molecule for subsequent reduction steps.^[13] Finally, due to the higher electron affinity of Cu, the energetic electrons can readily reach the Cu nanoparticles for syngas production via the intimate Cu-ZnO interface.

The morphology structure and chemical component of the Cu-ZnO/GaN/n⁺-p Si heterostructures were studied by scanning




Figure 1. (a) Schematic illustration of Cu-ZnO/GaN/n⁺-p Si photocathode (not drawn to scale). (b) SEM images of GaN nanowires grown on a p-n junction Si. (c) SEM and (d) TEM images of Cu-ZnO decorated GaN nanowires. Inset of (d), and (e): HRTEM images of the interface between Cu, ZnO and GaN.

electron microscopy (SEM), transmission electron microscopy (TEM) and X-ray photoelectron spectroscopy (XPS). The SEM image of GaN/n⁺-p Si (Figure 1b) shows the GaN nanowires are vertically aligned on the Si substrate with lengths and diameters about 150 nm and 30 nm, respectively. After the deposition of Cu-ZnO, it can be seen that the upper part of the GaN nanowires are covered by a network of ZnO nanosheets with sizes in the ranges of 300-500 nm and thicknesses about 10 nm (Figure 1c). A range of Cu nanoparticles of 3-10 nm size are deposited on the surface of ZnO nanosheets (Figures 1c-d). The presence of both Cu and Zn in the composites was confirmed by energy-dispersive X-ray (EDX) spectrum (Figure S2). High-resolution (HR) TEM images in Figures 1d-e show that intimate contacts are formed between GaN nanowires, ZnO nanosheets and Cu nanoparticles, which are beneficial for efficient transport of photogenerated charge carriers.^[14] The lattice fringe of 0.21 nm corresponds to the (111) facet of Cu (inset of Figure 1d). Both GaN and ZnO show interplanar spacing of 0.26 nm between the two adjacent (002) lattice planes of wurtzite structure, indicating the growth along <0001> direction (c-axis). The <0001> orientation of GaN nanowires is confirmed by the presence of (002) and (004) diffraction peak from X-ray diffraction (XRD) measurement (Figure S3). The XPS analysis indicates metallic Cu (Cu⁰) and Zn²⁺ from ZnO (Figure S4).

PEC performance of the Cu-ZnO/GaN/n⁺-p Si photocathode was evaluated in a conventional three-electrode cell in CO₂-saturated aqueous solution of 0.5 M KHCO₃ (pH 8) under 300 W xenon lamp irradiation. Figure 2a shows the FEs for CO and H₂ as a function of applied potential between +0.07 V and -0.33 V vs.




Figure 2. (a) FEs for CO (grey bars) and H₂ (red bars) of Cu-ZnO/GaN/n⁺-p Si photocathode as a function of potential in CO₂-saturated 0.5 M KHCO₃ solution (pH 8). (b) J-V curves in Ar and CO₂-saturated 0.5 M KHCO₃ solution. The dashed line shows the standard potential for CO₂ reduction to CO at pH 8.




Figure 3. Chronoamperometry data and FEs for CO and H_2 of Cu-ZnO/GaN/n⁺ p Si photocathode at -0.23 V vs. RHE.

RHE. The chronoamperometry data and photocurrent-potential curve under chopped illumination are shown in Figures S5-S6. At an applied potential of +0.07 V, CO is the dominant product with a FE of 70% and the remaining balance of photocurrent drives the reduction of proton to form H₂. By tuning the potential from +0.07 V to -0.33 V, the CO/H₂ ratio can be adjusted in a large range between 2 : 1 and 1 : 4. At -0.23 V, a CO/H₂ ratio of 1 : 2 is obtained, which is a desirable composition of syngas mixtures for methanol and liquid fuels production.^[1] The decreasing of CO selectivity by applying a more negative potential in this study is consistent with previously reported results over Cu-based cathodes.^[15] At low applied bias, CO can be formed at relatively high rate due to the catalytic effect of Cu cathode and lower overpotential required compared to the formation of other CO2 reduction products (e.g. CH₄). As the overpotential increases, the FE for CO decreases because kinetic mass transfer of CO₂ to the electrode surface instead of thermodynamics becomes the ratedetermining step for the CO formation. It was reported that local pH near the cathode could be substantially higher than that in the bulk electrolyte at high-current-density operation (> 1 mA cm^{-2}), owing to the release of OH^{-} from CO_{2} reduction and H_{2} evolution. The large increase in pH at the cathode surface would lead to a great reduction in the local CO2 concentration and thus form a kinetic and mass transport limitation for CO₂ reduction.^[16] The kinetic limitation was evidenced by the fairly constant value of partial current density for CO in the high overpotential region (Figure S7). At all the applied potentials, a total FE of 103±5% was obtained for the co-generation of CO and H₂, with no appreciable amount of other gas products detected by GC. Besides, no liquid product (e.g. HCOOH and CH₃OH) was observed in the analysis of electrolyte by nuclear magnetic resonance (NMR) spectroscopy, suggesting a unity FE of our material system for syngas production.

Table 1. The reported low potentials and corresponding FEs for CO in aqueous PEC cell using various monolithic photocathode materials.

| Electrode | Co-catalyst | Electrolyte | Potential (V vs. RHE) ^[a] | FE (%) | Ref. |
|----------------|-------------|---------------------|---|-------------------|--------------|
| p-Si | - | KHCO ₃ | -0.62 | 12 | 5 |
| p-Si | Au | KHCO ₃ | -0.09 | 62 | 5 |
| p-Si | Ag | KHCO ₃ | -0.40 | 51 | 5 |
| p-Si | Cu | KHCO ₃ | -0.40 | 10 | 5 |
| p-CdTe | - | TEAP ^[b] | -0.35 | 78 | 6 |
| p-InP | - | TEAP | -0.35 | 31 ^[c] | 6 |
| p-ZnTe | - | KHCO ₃ | -0.20 | 8.4 | 7a |
| p-ZnTe | Au | KHCO ₃ | -0.10 | 26 ^[d] | 7b |
| GaN/n⁺-p Si | Cu/ZnO | KHCO ₃ | +0.07 | 70 | This work |

[a] Reported potentials were converted to RHE values by the following equation: $V_{RHE} = V + (0.059 * pH) + V_{Ref}$, Where $V_{Ref} = 0.244$ and 0.197 for SCE and Ag/AgCI respectively. [b] TEAP: tetraethylammonium perchlorate. [c] obtained at -0.55 V vs. RHE, the data at -0.35 V was not reported. [d] The highest FE reported in the system was 63% at -0.5 V vs. RHE.

To determine electrode activity with CO₂, a comparison study of photocurrent-potential curves under Ar and CO₂ atmosphere was conducted (Figure 2b). It was found that there was a strong photocurrent enhancement under the CO₂ atmosphere, which is attributed to the interaction between the electrode surface and CO₂ molecule for producing CO. To verify the evolved CO is derived from CO₂ reduction rather than other possible carbon impurities on the catalyst, we used high-purity ¹³CO₂ as the reactant to conduct the reaction. The ¹³CO₂ isotopic-labeling results showed a similar peak at the same retention time in the GC with ¹²CO₂ experiment; however, only a signal at m/z = 29 corresponding to ¹³CO appeared in the mass spectrum data (Figure S8). This provides direct evidence that the CO product is originated from the reduction of CO₂.

The operating stability of the photoelectrode is essential to their application. Figure 3 shows the chronoamperometry data and FEs for CO and H_2 at -0.23 V vs. RHE under constant illumination for 10 h. The electrode showed no appreciable decay in photocurrent density while maintaining a total near-unity FE for CO and H₂ co-generation. The CO/H₂ ratio in the products was kept nearly 1:2 during the 10 h period of operation, demonstrating the superior stability of the electrode. The turnover number (TON), defined as the ratio of the total amount of gas evolved (66.5 µmol) to Cu-ZnO catalyst (~0.05 $\mu mol,$ see Figure S9 for calculation details), reached 1330 after 10 h of photoelectrolysis, significantly out-performing the values recently reported for selective CO formation from CO₂ reduction.^[17] As a note, the TON reported in this study is underestimated because the calculation is based on the bulk catalyst instead of only surface sites (see supporting information for TON calculation considering only surface sites).

An important feature of our system is the high FE of 70% for CO achieved at underpotential of 180 mV (+0.07 V vs. RHE), suggesting that light energy is indeed used to drive the reaction. The reported low potentials and FEs for the reduction of CO_2 to CO in an aqueous PEC cell are compared in Table 1. Among various monolithic photocathodes, our material exhibits the lowest potential, which is 160 mV positive shifts compared with the lowest potential reported in the literature.^[5] It is worth noting that




Figure 4. (a) J-V curves. (b) FEs for CO at -0.33 V vs. RHE. (c) Proposed reaction mechanism for the photoreduction of CO₂ to produce CO on Cu-ZnO dual co-catalysts.

the onset potential can be further positively shifted by connecting our photocathode with a photovoltaic system. Very recently, Lee and co-workers achieved a very low onset potential of ~0.6 V vs. RHE in a photocathode-photovoltaic tandem device.^[7c] Moreover, the CO FE of 70% in this work represents one of the highest values reported in an aqueous PEC cell, which was even more remarkable considering the noble-metal-free component in the present material. The extremely low onset potential of our photocathode is attributed to its multi-functional hierarchical structures, which include the strong light harvesting of p-n junction Si, the efficient electron extraction and transport of GaN nanowire arrays, and the fast surface reaction kinetics of Cu-ZnO co-catalysts. Control experiments of photocurrent-potential test in the absence of one of the three components were conducted (Figure S10). The onset potentials (as taken from the potentials of 0.5 mA cm⁻²) of the photocathodes without p-n junction Si, GaN nanowires or Cu-ZnO co-catalysts are -0.63, -0.20 and -0.32 V vs. RHE respectively, which are at least 270 mV more negatively shifted compared to that of Cu-ZnO/GaN/n⁺-p Si (+0.07 V).

In order to gain insights into the high performance of Cu-ZnO/GaN/n⁺-p Si, PEC measurements were conducted with plain GaN/n*-p Si and with single Cu or ZnO co-catalyst. Photocurrentpotential curves (Figure 4a) show the photocurrent density is very small in the absence of any co-catalyst (0.6 mA cm⁻² at -0.33 V vs. RHE), and ZnO alone does not show any promotive effect. In contrast, Cu co-catalyst can greatly enhance the activity, resulting in a photocurrent density of ~6 mA cm⁻² at -0.33 V. Compared to bare Cu, significantly higher photocurrent density of 10 mA cm⁻² at -0.33 V is attained when Cu and ZnO are loaded simultaneously. A comparison study of FEs for CO of different samples at -0.33 V is shown in Figure 4b. It is clear that Cu has negligible effect on the selectivity for CO₂ reduction to CO, whereas the CO formation selectivity increases about eight times from 1.7% to 14.3% by loading ZnO on GaN/n+-p Si. In addition, the FE for CO of Cu-ZnO/GaN/n+-p Si is the highest (20%), which is ten times higher than that of Cu/GaN/n+-p Si (2%). The important role of ZnO in the selective CO2 reduction is further confirmed by the comparison of FEs for CO at other potentials range from +0.07 V to -0.23 V (Figure S11). Moreover, CO2 adsorption-desorption testing results (Figure S12) revealed the amount of CO2 adsorption capacity over Cu-ZnO/GaN/n*-p Si was 0.95 µmol cm-2, which was 3.4 times higher than that of Cu/GaN/n+-p Si (0.28 µmol cm-2). Note that the CO2 adsorption amount of plain GaN/n+-p Si (0.24 µmol cm-2) was only slightly smaller than that of Cu/GaN/n+-p Si, indicating the low propensity

of Cu co-catalyst for CO2 adsorption. On the basis of the above results, the reaction mechanism of CO2 photoreduction to produce CO on Cu-ZnO dual co-catalysts is proposed (Figure 4c). CO2 molecule is intially adsorbed and activated on ZnO to break its linear symmetry for the formation of destabilized bent configuration. Then it migrates onto Cu to proceed through a [2] series of elementary steps via the carboxyl (*COOH) intermediate involving the consecutive transfer of protons and electrons, resulting in the cleavage of C-O bond and the formation of CO product.[18] The proposed mechanism was further supported by a systematic study of the effect of Cu/Zn ratio on the product selectivity (Figure S13). It was found that the highest FE for CO was obtained at a composition with a balanced reaction of CO2 adsorption on ZnO and proton-coupled electron transfer on Cu. The capability of ZnO to enhance the selectivity for CO₂ reduction to CO was also verified in other similar systems, by coupling ZnO [5] with other metal co-catalysts such as Au and Ag. The FEs for CO [6] with Au-ZnO or Ag-ZnO dual co-catalysts are 1.9 and 2.4 times higher than that with Au or Ag alone, respectively (Figure S14). SEM tests revealed that the sizes of Au or Ag particles were in the range of 50-100 nm and small interface area was formed between the metal and ZnO nanosheets (Figures S15-S16), which may cause less synergetic effect for selective CO2 In addition to the electronic effect to influence the binding of [9]

CO₂, there is a geometric effect of ZnO nanosheet to function as an excellent 2D support for the enhanced dispersion of Cu nanoparticles to increase the Cu surface area for the reactions. The SEM image of Cu/GaN/n+-p Si shows the sizes of Cu are in the range between 10 and 50 nm, with some particles aggregate to form large clusters up to 100 nm (Figure S17). The possible effect of change in the oxidation states of Cu in the presence of ZnO was ruled out from XPS analysis (Figure S18). However, the Cu2p peak of Cu-ZnO/GaN/n+-p Si was negatively shifted by ~0.4 eV compared to that of Cu/GaN/n+-p Si, which could be attributed to the strong interaction between Cu and ZnO due to the electron transfer from ZnO to Cu.^[19] In the intimate Cu-ZnO interface, one can have adsorption/reaction sites with complementary chemical properties, truly bifunctional sites that cannot be achieved by either Cu or ZnO alone.

In conclusion, we have demonstrated a monolithic photocathode for efficient, stable and tunable syngas production from CO2 and H2O reduction in an aqueous PEC cell. An unprecedented TON of 1330 and a high FE of 70% for CO at underpotential of 180 mV were achieved by integrating the strong light absorption capability of p-n junction Si and efficient electron extraction effect of GaN nanowire arrays with the fast surface reaction kinetics of Cu-ZnO co-catalysts. It was found that the combination of Cu and ZnO offered complementary chemical properties that lead to special reaction pathways not seen in Cu or ZnO alone. This work opens up opportunities to develop sustainable and carbon-neutral syngas production from the reduction of CO₂ and H₂O using solar energy with rationally designed heterostructures.

Acknowledgements

reduction to CO.

This work was supported by the Natural Sciences and Engineering Research Council of Canada (NSERC) and the Climate Change and Emissions Management Corporation (CCEMC). The authors wish to thank Dr. Lu Li for the GC-MS tests of ¹³C-labeled isotope experiment.


Keywords: Energy conversion • Semiconductors • Cocatalyst • CO₂ reduction • Solar fuel

- [1] A. Indarto, J. Palguandi, Syngas production, application and environmental impact, Nova Science Publishers, New York, 2013.
- G. Centi, S. Perathoner, Green Carbon Dioxide: Advances in CO2 Utilization, Wiley-VCH, Weinheim, 2014.
- [3] a) V. N. Nguyen, L. Blum, Chem. Ing. Tech. 2015, 87, 354-375; b) F. Li, J. Lau, S. Licht, Adv. Sci. 2015, 1500260; c) N. R. de Tacconi, H. K. Timmaji, W. Chanmanee, M. N. Huda, P. Sarker, C. Janaky, K. Rajeshwar, ChemPhysChem 2012, 13, 2945-2955.
- [4] a) B. Kumar, M. Llorente, J. Froelich, T. Dang, A. Sathrum, C. P. Kubiak, Annu. Rev. Phys. Chem. 2012, 63, 541-569; b) J. L. White, M. F. Baruch, J. E. Pander III, Y. Hu, I. C. Fortmeyer, J. E. Park, T. Zhang, K. Liao, J. Gu, Y. Yan, T. W. Shaw, E. Abelev, A. B. Bocarsly, Chem. Rev. 2015, 115, 12888-12935.
- R. Hinogami, Y. Nakamura, S. Yae, Y. Nakato, J. Phys. Chem. B 1998, 102, 974-980.
- H. Yoneyama, K. Sugimura, S. Kuwabata, J. Electroanal. Chem. 1988, 249, 143-153.
- [7] a) J. Jang, S. Cho, G. Magesh, Y. J. Jang, J. Y. Kim, W. Y. Kim, J. K. Seo, S. Kim, K. Lee, J. S. Lee, Angew. Chem., Int. Ed. 2014, 53, 5852-5857; b) Y. J. Jang, J.-W. Jang, J. Lee, J. H. Kim, H. Kumagai, J. Lee, T. Minegishi, J. Kubota, K. Domen, J. S. Lee, Energy Environ. Sci. 2015, 8, 3597-3604; c) Y. J. Jang, I. Jeong, J. Lee, J. Lee, M. J. Ko, J. S. Lee, ACS Nano 2016, 10, 6980-6987.
- [8] a) S. Fan, B. AlOtaibi, S. Y. Woo, Y. Wang, G. A. Botton, Z. Mi, Nano Lett. 2015, 15, 2721-2726; b) Y. Wang, S. Fan, B. AlOtaibi, Y. Wang, L. Li, Z. Mi, Chem. Eur. J. 2016, 22, 8809-8813.
- a) M. G. Kibria, R. Qiao, W. Yang, I. Boukahil, X. Kong, F. A. Chowdhury, M. L. Trudeau, W. Ji, H. Guo, F. J. Himpsel, L. Vayssieres, Z. Mi, Adv. Mater. DOI: 10.1002/adma.201602274; I) M. G. Kibria, Z. Mi, J. Mater. Chem. A 2016. 4. 2801-2820.
- [10] a) A. M. Mozharov, A. D. Bolshakov, D. A. Kudryashov, N. V. Kryzhanovskaya, G. E. Cirlin, I. S. Mukhin, J. C. Harmand, M. Tchernysheva, J. Phys. Conf. Ser. 2015, 643 012115; b) C. Liu, N. P. Dasgupta, P. Yang, Chem. Mater. 2014, 26, 415-422.
- [11] R. D. Vispute, V. Talyansky, S. Choopun, R. P. Sharma, T. Venkatesan, M. He, X. Tang, J. B. Halpern, M. G. Spencer, Y. X. Li, L. G. Salamanca-Riba, A. A. Iliadis, K. A. Jones, Appl. Phys. Lett. 1998, 73, 348.
- K. Maeda, T. Takata, M. Hara, N. Saito, Y. Inoue, H. Kobayashi, K. [12] Domen, J. Am. Chem. Soc. 2005, 127, 8286-8287.
- a) Y. Wang, R. Kovacik, B. Mever, K. Kotsis, D. Stodt, V. Staemmler, H. [13] Qiu, F. Traeger, D. Langenberg, M. Muhler, C. Woll, Angew. Chem. Int . Ed. 2007, 46, 5624-5627; b) H. Noei, C. Woll, M. Muhler, Y. Wang, J. Phys. Chem. C 2011, 115, 908-914; c) B. Mei, A. Becerikli, A. Pougin, D. Heeskens, I. Sinev, W. Grunert, M. Muhler, J. Strunk, J. Phys. Chem. C 2012, 116, 1431814327.
- E. S. Kim, N. Nishimura, G. Magesh, J. Y. Kim, J. W. Jang, H. Jun, J. [14] Kubota, K. Domen, J. S. Lee, J. Am. Chem. Soc. 2013, 135, 5375-5383.
- [15] a) D. Raciti, K. J. Livi, C. Wang, Nano Lett. 2015, 15, 6829-6835; b) C. W. Li, M. W. Kanan, J. Am. Chem. Soc. 2012, 134, 7231-7234; c) K. P. Kuhl, T. Hatsukade, E. R. Cave, D. N. Abram, J. Kibsgaard, T. F. Jaramillo, J. Am. Chem. Soc. 2014, 136, 14107-14113.
- [16] a) M. R. Singh, E. L. Clark, A. T. Bell, Phys. Chem. Chem. Phys. 2015, 17, 18924-18936; b) E. E. Barton, D. M. Rampulla, and A. B. Bocarsly, J. Am. Chem. Soc. 2008, 130, 6342-6344; c) N. Gupta, M. Gattrell, B. MacDougall, J. Appl. Electrochem. 2006, 36, 161-172.
- [17] a) H. Takeda, K. Ohashi, A. Sekine, O. Ishitani, J. Am. Chem. Soc. 2016. 138, 4354-4357; b) T. E. Rosser, C. D. Windle, E. Reisner, Angew. Chem., Int. Ed. 2016, 55, 7388-7392.
- [18] a) A. A. Peterson, F. Abild-Pedersen, F. Studt, J. Rossmeisl, J. K. Nørskov, Energy Environ. Sci. 2010, 3, 1311-1315; b) S. Back, M. S. Yeom, Y. Jung, ACS Catal. 2015, 5, 5089-5096.
- [19] F. Liao, Y. Huang, J. Ge, W. Zheng, K. Tedsree, P. Collier, X. Hong, S. C. Tsang, Angew. Chem. Int. Ed. 2011, 50, 2162-2165.

filled in by editorial staff)) Received: ((will be the Published online on ((will be filled in by the editorial staff))

COMMUNICATION

Mixture is better: Syngas (CO+H₂ mixtures) with tunable composition are synthesized from the reduction of CO_2 and H_2O in an aqueous photoelectrochemcal cell. А benchmark turnover number of 1330 and a high Faradaic efficiency of 70% for CO at underpotential of 180 mV are acheived. This is attributed to the coupling effects of strong light harvesting of p-n junction Si, efficient electron extraction of GaN nanowire arrays, and fast surface reaction kinetics of Cu-ZnO co-catalysts.



Sheng Chu, Shizhao Fan, Yongjie Wang, David Rossouw, Yichen Wang, Gianluigi A. Botton and Zetian Mi*

Page No. – Page No.

Tunable Syngas Production from CO₂ and H₂O in an Aqueous Photoelectrochemical Cell